

Issue Date: June 28, 2012

INTRODUCING CliQ II DIN RAIL 48V 240W (5A)



- POWER BOOST UP TO **150%** FOR 5 SEC.
- **HIGH EFFICIENCY: > 90%**
- PARALLEL OPERATION OF UP TO **FIVE** POWER SUPPLIES

For more information, visit www.DeltaPSU.com

CliQ II DIN Rail 48V 240Watts is the latest offering from Delta CliQ II DIN Rail Power Supply series. The 48V power supplies are typically used in telecom equipment applications including POE. In the tradition of the CliQ Series, the CliQ II 48V products are IP20 certified, come in a tough anti-corrosion aluminum casing and features high efficiency without output power derating for the entire range of input voltage from 85Vac to 264Vac. The pluggable terminal block on the 240W type also enables safe and fast connections.

Applications

- POE Application
- Instrumentation & Measurement
- General Industrial Applications

DRP48V240W1BA SPECIFICATIONS

Input Voltage Range	85-264Vac
Output Voltage Range	48-56Vdc
Output Current	5.0A
Inrush Current	< 35A @ 115Vac & 230Vac
Power Factor	> 0.96 @ 115Vac, > 0.90 @ 230Vac
Dimensions (L x W x D)	121mm x 85mm x 124.1mm
Weight	0.97kg
Ambient Temperature	-25°C to +80°C

Upcoming Events

- **Automation 2012**
Location: Mumbai, India
Dates: 7 – 10 September 2012
- **KOFAS 2012**
Location: Goyang, Korea
Dates: 11 – 14 September 2012
- **2012 NECA Energy Forum**
Location: Las Vegas, Nevada, USA
Dates: 29 Sept – 2 Oct 2012
- **Electronica 2012**
Location: Munich, Germany
Dates: 13 – 16 November 2012

PMT PANEL MOUNT POWER SUPPLY SERIES



- 24V 35W
- 24V 50W

*Available for shipment in July '12