

Issue Date: July 18, 2013

Delta Extends PMC Panel Mount Power Supply Series with 48V 150W Product



Also Available:

- ▲ IP20 Connector



- ▲ Front Face Connector



- ▲ Harness Connector



The PMC Panel Mount Power Supply series now offers 150W output power with 48V output voltage. The single output product (PMC-48V150W1B□) comes with universal AC input at 85Vac to 264Vac and has built-in active PFC circuit to achieve high PF (Power Factor) value. The product is encased in a full corrosion resistant aluminium body and complies with harmonic current emission (EN 61000-3-2), Class A. The sturdy PMC-48V150W1B□ will withstand shock (30G) and vibration (5G) according to IEC 60068-2 standard.

Highlights & Features

- Universal AC input voltage range
- Full Aluminium casing for lightweight and corrosion resistant handling
- High PF > 0.99 @ 115Vac
- Conforms to harmonic current IEC/EN 61000-3-2, Class A
- High MTBF > 700,000 hrs as per Telcordia SR-332
- Overvoltage / Overcurrent / Over Temperature / Short Circuit Protections

The PMC-48V150W1B□ is certified to major safety standards including IEC/EN/UL 60950-1 while fully compliant with RoHS Directive 2011/65/EU for environmental protection. Additionally, the product is certified for EMC according to EN 55022 for Information Technology Equipment (ITE) radio-frequency equipment and EMS according to EN 55024.


AVAILABLE FOR SHIPMENT FROM JULY 2013 ONWARDS.

New models are introduced on a regular basis. For more information or enquiries, please do not hesitate to contact your local Delta Electronics distributor or visit www.DeltaPSU.com.

Upcoming Events

- **Techno-Frontier 2013**
Location: Tokyo, Japan
Dates: 17 – 19 July 2013
- **Automation 2013**
Location: Mumbai, India
Dates: 23 – 26 September 2013
- **All-Energy Australia 2013**
Location: Melbourne, Australia
Dates: 9 – 10 October 2013

DIN RAIL ACCESSORIES



Transform your Panel Mount PSU into a DIN Rail PSU with our accessories.